

2011 BMW F 800 GS

MSRP: \$11,455.00* Destination charge (not included in MSRP): \$495



Copyright 2010 BMW of North America, LLC., Woodcliff Lake, New Jersey all rights reserved.
 *Actual price determined by dealer. Price excludes taxes, license, options and handling charge.
 Prices and specifications subject to change without notice.

Engine		Wheels and Tires	
Type	Water cooled twin cylinder 4 stroke	Front Wheel	2.15 x 21 spoked wheel with aluminum rim
Bore x Stroke	82 mm x 76 mm	Rear Wheel	4.25 x 17 spoked wheel with aluminum rim
Displacement	798 cc	Front Tire	90/90 x 21
Horsepower	85 bhp @ 7500 rpm	Rear Tire	150/70 x 17
Torque	62 lb/ft @ 5750 rpm	Dimensions	
Compression Ratio	12.0 :1	Overall Length	91.0 inches
Valve Gear	DOHC chain driven with cam followers	Overall Width	34.2 inches
Valves	2 x 32 mm intake / 2 x 27.5 mm exhaust	Wheelbase	62.1 inches
Valves / Cylinder	4	Ground Clearance	Info. Unavailable
Engine Oil Capacity	3.1 quarts	Seat Height	34.6 inches
Engine Management	BMW Engine Controller - BMS K	Steering Angle	64.0 degrees
Fuel Requirement	Premium Unleaded	Front Wheel Trail	4.6 inches
Fuel Tank	HDPE, internal pump and internal filter	Weight - Dry	392 lbs. excluding options & accessories
Fuel Capacity	4.2 U.S. gallons	Weight - Wet	455 lbs. excluding options & accessories
Charging System	400 Watts @ 14 Volts	Maximum Load	975 lbs. GVWR
Battery	12 Volts 14 Amps/hour maintenance-free	Available Colors	
Cooling System	50/50 water/anti-freeze mix, single radiator	Code Price	Description
Drivetrain		751 N / C	Alpine White
Primary Drive	1:1.943	N24 N / C	Lava Orange Metallic / Black Silk Shining
Clutch	Wet multi plate	Standard Equipment	
1st Gear Ratio	2.46:1	588 N / C	White Turn Signals
2nd Gear Ratio	1.75:1	Available Equipment	
3rd Gear Ratio	1.38:1	519 \$250	Heated Hand Grips
4th Gear Ratio	1.17:1	524 \$900	ABS
5th Gear Ratio	1.04:1	539 \$295	On Board Computer
6th Gear Ratio	0.96:1	603 \$395	Anti-Theft Alarm
Final Drive System	Chain	636 \$175	Center Stand
Final Drive Ratio	2.62:1	774 N / C	Low Seat
Frame and Suspension			
Frame	Tubular steel trellis frame		
Front Suspension	UPSD fork 45 mm		
Front Travel	9.0 inches		
Rear Suspension	Double sided aluminum swingarm		
Rear Travel	8.5 inches		
Brakes			
Brake System	Front and rear disc with optional ABS		
Front Brakes	Brembo 2 piston floating calipers		
Front Rotor	11.8 inch dual rotors		
Rear Brake	Single piston floating caliper		
Rear Rotor	10.4 inch single, fixed rotor		
Actuation Method	Hydraulic, DOT 4 fluid type		