

2011 BMW R 1200 GS Adventure

MSRP: \$17,250.00* Destination charge (not included in MSRP): \$495



Copyright 2010 BMW of North America, LLC., Woodcliff Lake, New Jersey all rights reserved.
 *Actual price determined by dealer. Price excludes taxes, license, options and handling charge.
 Prices and specifications subject to change without notice.

Engine		Wheels and Tires	
Type	Air-cooled/oil-cooled Boxer twin-cylinder	Front Wheel	2.50 x 19 cross-spoke
Bore x Stroke	101.0 mm x 73.0 mm	Rear Wheel	4.00 x 17 cross-spoke
Displacement	1170 cc	Front Tire	110/80 x 19 tubeless
Horsepower	110 bhp @ 7750 rpm	Rear Tire	150/70 x 17 tubeless
Torque	88 lb/ft @ 6000 rpm	Dimensions	
Compression Ratio	12.0 :1	Overall Length	88.6 inches
Valve Gear	DOHC, chain driven, radial layout w/ cam followers	Overall Width	37.6 inches
Valves	2 x 39 mm intake / 2 x 33 mm exhaust	Wheelbase	59.5 inches
Valves / Cylinder	Four	Ground Clearance	Info. Unavailable
Engine Oil Capacity	4.2 quarts	Seat Height	35.0 inches
Engine Management	BMW Engine Controller - BMS K+	Steering Angle	63.8 degrees
Fuel Requirement	Premium Unleaded	Front Wheel Trail	3.8 inches
Fuel Tank	HDPE, internal pump and internal filter	Weight - Dry	492 lbs. excluding options&accessories
Fuel Capacity	8.7 U.S. gallons including 1 gallon reserve	Weight - Wet	564 lbs. excluding options&accessories
Charging System	720 Watts @ 14 Volts	Maximum Load	1045 lbs. GVWR
Battery	12 Volts 14 Amps/hour low maintenance	Available Colors	
Cooling System	Air and thermostatically controlled oil cooling	Code Price	Description
Drivetrain		M11 N / C	Smoke Gray Metallic Matt
Primary Drive	1:1.737	N03 N / C	Shine Yellow Metallic
Clutch	180 mm dry, single plate with hydraulic actuation	Standard Equipment	
1st Gear Ratio	2.60:1	588 N / C	White Turn Signals
2nd Gear Ratio	1.70:1	589 N / C	Hand Protection
3rd Gear Ratio	1.30:1	631 N / C	Enduro Transmission
4th Gear Ratio	1.07:1	636 N / C	Center Stand
5th Gear Ratio	0.94:1	771 N / C	Cross Spoke Wheels
6th Gear Ratio	0.85:1	Available Equipment	
Final Drive System	Enclosed driveshaft with two universal joints	350 \$150	Chrome Exhaust
Final Drive Ratio	2.91:1	416 \$800	Enduro ESA
Frame and Suspension		519 \$250	Heated Hand Grips
Frame	Tubular steel trellis frame	530 \$250	Tire Pressure Monitor (TPM)
Front Suspension	BMW Telelever	539 \$295	On Board Computer (Incl. Oil Level Warning)
Front Travel	8.3 inches	562 \$450	Fog Light
Rear Suspension	BMW EVO Paralever	603 \$395	Anti-Theft Alarm
Rear Travel	8.7 inches	630 \$1100	Integral ABS (Disconnectable)
Brakes		633 N / C	Off-Road Tires
Brake System	BMW	650 \$400	Enduro ASC (only with 630)
Front Brakes	Two, four-piston fixed calipers	680 \$350	Saddle Bag Mounts
Front Rotor	12.0 inch Dual Rotors		
Rear Brake	Single, two-piston floating caliper		
Rear Rotor	10.4 inch single, fixed rotor		
Actuation Method	Hydraulic, DOT 4 fluid type		