2013 BMW F 700 GS

10.4 inch single rotor

Hydraulic, DOT 4 fluid type

Rear Rotor
Actuation Method

MSRP: \$9,990.00* Destination charge (not included in MSRP): \$495



Copyright 2012 BMW of North America, LLC., Woodcliff Lake, New Jersey all rights reserved. *Actual price determined by dealer. Price excludes taxes, license, options and handling charge. Prices and specifications subject to change without notice.

Engine		Wheels and Tires	
Туре	Water cooled twin cylinder 4 stroke	Front Wheel	2.50 x 19 cast aluminum
Bore x Stroke	82 mm x 76 mm	Rear Wheel	3.50 x 17 cast aluminum
Displacement	798 cc	Front Tire	110/80 x 19 tubeless
Horsepower	75 bhp @ 7300 rpm	Rear Tire	140/80 x 17 tubeless
Torque	57 lb/ft @ 5300 rpm	Dimensions	1
Compression Ratio	12.0 :1	Overall Length	89.7 inches
Valve Gear	DOHC chain driven with cam followers	Overall Width	35.0 inches
Valves	2 x 32 mm intake / 2 x 27.5 mm exhaust	Wheelbase	61.5 inches
Valves / Cylinder	4	Ground Clearance	Info. Unavailable
Engine Oil Capacity	3.1 quarts	Seat Height	32.3 inches
Engine Management	BMW Engine Controller - BMS K	Steering Angle	64.0 degrees
Fuel Requirement	Premium Unleaded	Front Wheel Trail	3.7 inches
Fuel Tank	HDPE, internal pump and internal filter	Weight - Dry	410 lbs. excluding options & accessories
Fuel Capacity	4.2 U.S. gallons	Weight - Wet	461 lbs. excluding options & accessories
Charging System	400 Watts @ 14 Volts	Maximum Load	961 lbs. GVWR
Battery	12 Volts 14 Amps/hour maintenance-free	Available Colors	
Cooling System	50/50 water/anti-freeze mix, single radiator	Code Price	Description
Drivetrain		N39 N/C	Red Apple Metallic
Primary Drive	1:1.943	N50 N/C	Ostra Grey Metallic Matt
Clutch	Wet multi plate	N99 N/C	Glacier Silver Metallic
1st Gear Ratio	2.46:1	Available Equipment	
2nd Gear Ratio	1.75:1	416 \$350	Electronic Suspension Adjustment (ESA)
3rd Gear Ratio	1.38:1	430 \$795	Safety Package (416, 530, 650)
4th Gear Ratio	1.17:1	431 \$505	Comfort Package (519, 539, 636, 681)
5th Gear Ratio	1.04:1	499 \$250	Low Suspension (not w/416, 430, 431, 636, 775,ZLS)
6th Gear Ratio	0.96:1	519 \$250	Heated Hand Grips
Final Drive System	Chain	530 \$250	Tire Pressure Monitor (TPM)
Final Drive Ratio	2.47:1 (17 / 42 tooth sprockets)	539 \$295	On Board Computer
Frame and Suspension		603 \$395	Anti-Theft Alarm
Frame	Tubular steel trellis frame	636 \$175	Center Stand (not with 499)
Front Suspension	41 mm telescopic fork	650 \$400	ASC
Front Travel	7.1 inches	681 \$150	Saddle Bag Mounts
Rear Suspension	Double sided aluminum swingarm	774 N/C	Low Seat
Rear Travel	6.7 inches	775 \$145	Comfort Seat (not w/ 499, 774, ZLS)
Brakes		ZLS \$580	Low Suspension Plus Pckg (499, 519, 539, 681)
Brake System	BMW Motorrad ABS (Switchable) - Standard		
Front Brakes	Dual floating discs, two-piston floating calipers		
Front Rotor	11.8 inch dual floating rotors		
Rear Brake	Single disc, single-piston floating caliper		