2014 BMW C 650 GT

Front Brakes

Front Rotor

Rear Brake

Rear Rotor

Actuation Method

Dual discs, two-piston floating calipers


10.6 inch dual rotors

10.6 inch single rotor

Single disc

Hydraulic

MSRP: \$9,990.* Destination charge (not included in MSRP): \$495





Engine		Wheels and Tires	
Туре	Liquid-cooled in-line twin, 4-stroke	Front Wheel	3.50 x 15 cast aluminum
Bore x Stroke	79 mm x 66 mm	Rear Wheel	4.50 x 15 cast aluminum
Displacement	647 cc	Front Tire	120/70 x ZR 15
Horsepower	60 bhp @ 7500 rpm	Rear Tire	160/60 x ZR 15
Torque	49 lb/ft @ 6000 rpm	Dimensions	
Compression Ratio	11.6 :1	Overall Length	87.3 inches
Valve Gear	DOHC, chain-driven with bucket tappets	Overall Width	36.0 inches
Valves	2 x 31.5 mm intake / 2 x 27.1 mm exhaust	Wheelbase	62.6 inches
Valves / Cylinder	Four	Ground Clearance	Info. Unavailable
Engine Oil Capacity	3.5 quarts	Seat Height	31.7 inches
Engine Management	BMS-E BMW Digital Engine Management	Steering Angle	64.6 degrees
Fuel Requirement	Premium Unleaded	Front Wheel Trail	3.6 inches
Fuel Tank	Info. Unavailable	Weight - Dry	536 lbs. excluding options & accessories
Fuel Capacity	4.2 U.S. gallons	Weight - Wet	575 lbs. excluding options & accessories
Charging System	588 Watts @ 14 Volts	Maximum Load	981 lbs. GVWR
Battery	12 Volts 12 Amps/hour maintenance-free AGM	Available Colors	
Cooling System	Water-cooling with oil heat exchanger	Code Price	Description
Drivetrain		N43 N / C	Sapphire Black Metallic
Primary Drive	1.06	NC7 N/C	Quartz Blue Metallic
Clutch	CVT with centrifugal clutch	ND4 N/C	Havanna Metallic
1st Gear Ratio	Info. Unavailable	Standard Equipment	
2nd Gear Ratio	Info. Unavailable	N/C	Stepless Power Adjustable Windshield
3rd Gear Ratio	Info. Unavailable	N/C	Multifunction Display w/ On Board Computer
4th Gear Ratio	Info. Unavailable	Available Equipment	
5th Gear Ratio	Info. Unavailable	198 \$605	Highline Package (518, 519, 530)
6th Gear Ratio	Info. Unavailable	262 \$455	Highline Package Low Seat (519, 530, 774)
Final Drive System	Oil-immersed roller chain	518 \$PKG	Heated Seat (only with 198 package)
Final Drive Ratio	1:1.687 (16/27 teeth)	519 \$PKG	Heated Grips (only with 198 or 262 packages)
Frame and Suspension		530 \$PKG	TPM (Tire Pressure Monitor) (only with 198 or 262)
Frame	Tubular steel with die-cast aluminum sections	603 \$395	Anti-Theft Alarm
Front Suspension	Upside-down fork, 40 mm diameter	774 N/C	Low Saddle Seat (no seat heating)
Front Travel	4.5 inches		
Rear Suspension	Single-sided swingarm		
Rear Travel	4.5 inches		
Brakes			
Brake System	BMW Motorrad ABS - Standard		
	±		