## 2014 BMW F 800 GS

Rear Brake

Rear Rotor
Actuation Method

Single disc, single-piston floating caliper

10.4 inch single rotor

Hydraulic, DOT 4 fluid type

## MSRP: \$12,090.00\* Destination charge (not included in MSRP): \$495



Copyright 2013 BMW of North America, LLC., Woodcliff Lake, New Jersey all rights reserved. \*Actual price determined by dealer. Price excludes taxes, license, options and handling charge. Prices and specifications subject to change without notice.

Engine		Wheels and Tires	
Туре	Water cooled twin cylinder 4 stroke	Front Wheel	2.15 x 21 spoked wheel with aluminum rim
Bore x Stroke	82 mm x 76 mm	Rear Wheel	4.25 x 17 spoked wheel with aluminum rim
Displacement	798 cc	Front Tire	90/90 x 21
Horsepower	85 bhp @ 7500 rpm	Rear Tire	150/70 x 17
Torque	61 lb/ft @ 5750 rpm	Dimensions	
Compression Ratio	12.0 :1	Overall Length	91.3 inches
Valve Gear	DOHC chain driven with cam followers	Overall Width	37.2 inches
Valves	2 x 32 mm intake / 2 x 27.5 mm exhaust	Wheelbase	62.1 inches
Valves / Cylinder	4	Ground Clearance	Info. Unavailable
Engine Oil Capacity	3.1 quarts	Seat Height	34.6 inches
Engine Management	BMW Engine Controller - BMS K	Steering Angle	64.0 degrees
Fuel Requirement	Premium Unleaded	Front Wheel Trail	4.6 inches
Fuel Tank	HDPE, internal pump and internal filter	Weight - Dry	421 lbs. excluding options & accessories
Fuel Capacity	4.2 U.S. gallons	Weight - Wet	472 lbs. excluding options & accessories
Charging System	400 Watts @ 14 Volts	Maximum Load	979 lbs. GVWR
Battery	12 Volts 14 Amps/hour maintenance-free	Available Colors	
Cooling System	50/50 water/anti-freeze mix, single radiator	Code Price	Description
Drivetrain		751 N/C	Alpine White
Primary Drive	1:1.943	NA1 N/C	Cordoba Blue
Clutch	Wet multi plate	NA2 N/C	Kalamata Metallic Matt
1st Gear Ratio	2.46:1	Available Equipment	
2nd Gear Ratio	1.75:1	218 \$PKG	Off Road Mode for ABS & ASC (only w/ 235 package)
3rd Gear Ratio	1.38:1	235 \$675	Dynamic Package (includes 218, 416, 650)
4th Gear Ratio	1.17:1	416 \$350	Electronic Suspension Adjustment (ESA)
5th Gear Ratio	1.04:1	431 \$505	Comfort Package (includes 519, 539, 636, 681)
6th Gear Ratio	0.96:1	499 \$250	Low Suspension (not w/416, 430, 431, 636, 775,ZLS)
Final Drive System	Chain	519 \$250	Heated Hand Grips
Final Drive Ratio	2.62:1	539 \$295	On Board Computer
Frame and Suspension		603 \$395	Anti-Theft Alarm
Frame	Tubular steel trellis frame	633 N/C	Off-Road Tires
Front Suspension	Upside-down telescopic fork, 43 mm diameter	636 \$175	Center Stand (not with 499)
Front Travel	9.1 inches	650 \$400	ASC
Rear Suspension	Double sided aluminum swingarm	681 \$150	Saddle Bag Mounts
Rear Travel	8.5 inches	774 N/C	Low Seat
Brakes		775 \$145	Comfort Seat (not w/ 499, 774, ZLS)
Brake System	BMW Motorrad ABS (Switchable) - Standard	ZLS \$580	Low Suspension Plus Pckg (incl 499, 519, 539, 681)
Front Brakes	Dual floating discs, two-piston floating calipers		
Front Rotor	11.8 inch dual floating rotors		
	1	_	