2014 BMW F 800 GT

Rear Rotor

Actuation Method

10.4 inch single rotor

Hydraulic

MSRP: \$11,890.00* Destination charge (not included in MSRP): \$495



Copyright 2013 BMW of North America, LLC., Woodcliff Lake, New Jersey all rights reserved. *Actual price determined by dealer. Price excludes taxes, license, options and handling charge. Prices and specifications subject to change without notice.

Engine		Wheels and Tire	Wheels and Tires	
Туре	Water cooled twin cylinder 4 stroke	Front Wheel	3.50 x 17 cast aluminum	
Bore x Stroke	82 mm x 76 mm	Rear Wheel	5.50 x 17 cast aluminum	
Displacement	798 cc	Front Tire	120/70 x ZR 17	
Horsepower	90 bhp @ 8000 rpm	Rear Tire	180/55 x ZR 17	
Torque	63 lb/ft @ 5800 rpm	Dimensions		
Compression Ratio	12.0 :1	Overall Length	84.9 inches	
Valve Gear	DOHC, chain-driven with bucket tappets	Overall Width	35.5 inches	
Valves	2 x 32 mm mm intake / 2 x 27,5 mm mm exhaust	Wheelbase	59.6 inches	
Valves / Cylinder	4-Four	Ground Clearance	Info. Unavailable	
Engine Oil Capacity	3.2 quarts	Seat Height	31.5 inches	
Engine Management	BMW Engine Controller - BMS K+	Steering Angle	64.2 degrees	
Fuel Requirement	Premium Unleaded	Front Wheel Trail	3.7 inches	
Fuel Tank	HDPE, internal pump and internal filter	Weight - Dry	Info. Unavailable	
Fuel Capacity	4.0 U.S. gallons incl. approx. 0.8 gallon reserve	Weight - Wet	470 lbs. excluding options & accessories	
Charging System	400 Watts @ 14 Volts	Maximum Load	926 lbs. GVWR	
Battery	12 Volts 12 Amps/hour maintenance-free	Available Colors	Available Colors	
Cooling System	50/50 water/anti-freeze mix, single radiator	Code Price	Description	
Drivetrain		946 N/C	Dark Graphite Metallic	
Primary Drive	1:1.943	NB4 N/C	Valencia Orange Metallic	
Clutch	Multi-disc, oil bath, mechanical actuation	NB5 N/C	Light White	
1st Gear Ratio	2.46:1	Available Equipment		
2nd Gear Ratio	1.75:1	416 \$350	Electronic Suspension Adjustment (ESA)	
3rd Gear Ratio	1.38:1	430 \$795	Safety Package (includes 416, 530, 650)	
4th Gear Ratio	1.17:1	431 \$505	Comfort Package (includes 519, 539, 636, 681)	
5th Gear Ratio	1.04:1	519 \$250	Heated Hand Grips	
6th Gear Ratio	0.96:1	530 \$250	Tire Pressure Monitor (TPM)	
Final Drive System	Toothed belt drive	539 \$295	On Board Computer	
Final Drive Ratio	2.35:1	603 \$395	Anti-Theft Alarm	
Frame and Suspension		636 \$175	Center Stand	
Frame	Aluminum bridge-type frame w/ load-bearing engine	650 \$400	ASC	
Front Suspension	43 mm telescopic fork	681 \$150	Saddle Bag Mounts	
Front Travel	4.9 inches	774 N/C	Low Seat	
Rear Suspension	Alum. single sided swing arm, central spring strut	775 \$145	Comfort Seat	
Rear Travel	4.9 inches			
Brakes	Brakes			
Brake System	BMW Motorrad ABS - Standard			
Front Brakes	Dual floating discs, four-piston fixed calipers			
Front Rotor	12.6 inch dual floating rotors			
Rear Brake	Single disc, single-piston floating caliper			
·		1		