2015 BMW K 1300 S

Front Rotor

Rear Brake

Rear Rotor

Actuation Method

12.6 inch dual floating rotors

Hydraulic, DOT 4 fluid type

10.4 inch single rotor

Single disc, two-piston floating caliper

MSRP: \$15,855.00* Destination charge (not included in MSRP): \$495



Copyright 2014 BMW of North America, LLC., Woodcliff Lake, New Jersey all rights reserved. *Actual price determined by dealer. Price excludes taxes, license, options and handling charge. Prices and specifications subject to change without notice.

Engine		Wheels and Tire	Wheels and Tires	
Туре	Transverse, liquid cooled inline 4 cylinder	Front Wheel	3.50 x 17 cast aluminum	
Bore x Stroke	80 mm x 64 mm	Rear Wheel	6.0 x 17 cast aluminum	
Displacement	1293 cc	Front Tire	120/70 x 17 tubeless	
Horsepower	175 bhp @ 9250 rpm	Rear Tire	190/55 x 17 tubless	
Torque	103 lb/ft @ 8250 rpm	Dimensions		
Compression Ratio	13.0 :1	Overall Length	85.9 inches	
Valve Gear	DOHC, chain-driven with bucket tappets	Overall Width	35.6 inches	
Valves	2 x 32 mm mm intake / 2 x 27,5 mm mm exhaust	Wheelbase	62.4 inches	
Valves / Cylinder	Four	Ground Clearance	4.6 inches	
Engine Oil Capacity	3.7 quarts	Seat Height	32.3 inches	
Engine Management	BMW Engine Controller - BMS K+	Steering Angle	60.4 degrees	
Fuel Requirement	Premium Unleaded	Front Wheel Trail	4.1 inches	
Fuel Tank	HDPE, internal pump and internal filter	Weight - Dry	503 lbs. excluding options & accessories	
Fuel Capacity	5.0 U.S. gallons including 1 gallon reserve	Weight - Wet	560 lbs. excluding options & accessories	
Charging System	580 Watts @ 14 Volts	Maximum Load	1014 lbs. GVWR	
Battery	12 Volts 14 Amps/hour low maintenance	Available Colors		
Cooling System	Single Radiator, 50/50 water/anti-freeze mix	Code Price	Description	
Drivetrain		N0F \$PKG	Black Storm Metallic/ Light White/ Lupin Blue Met.	
Primary Drive	1.56	NB3 N/C	Sapphire Black Metallic / Dark Graphite Metallic	
Clutch	Multi-disc, oil bath, hydraulic actuation	Available Equipment		
1st Gear Ratio	2.39:1	177 \$450	Gear Shift Assistant	
2nd Gear Ratio	1.87:1	206 \$1440	Dynamic (includes 177, 416, 519, 530, 539, 650)	
3rd Gear Ratio	1.53:1	393 \$PKG	Special Model "Motorsport" Equipment (added w/424)	
4th Gear Ratio	1.29:1	416 \$900	ESA II	
5th Gear Ratio	1.14:1	424 \$3995	"Motorsport" Model (177,393,416,519,530,539,650)	
6th Gear Ratio	1.02:1	519 \$250	Heated Hand Grips	
Final Drive System	Enclosed driveshaft with two universal joints	530 \$250	Tire Pressure Monitor (TPM)	
Final Drive Ratio	2.82:1	539 \$295	On Board Computer	
Frame and Suspension		603 \$395	Anti-Theft Alarm	
Frame	Bridge-type cast aluminum	650 \$400	ASC	
Front Suspension	BMW Duolever	665 \$150	Luggage Grid	
Front Travel	4.5 inches	774 N/C	Low Seat (31.1 Inches)	
Rear Suspension	BMW EVO Paralever			
Rear Travel	5.3 inches			
Brakes				
Brake System	BMW Motorrad Integral ABS (Switchable) - Standard			
Front Brakes	Dual floating discs, four-piston fixed calipers			