2015 BMW F 800 R

Rear Rotor

Actuation Method

10.4 inch single fixed rotor

Hydraulic

MSRP: \$9,950.00* Destination charge (not included in MSRP): \$495



Copyright 2015 BMW of North America, LLC., Woodcliff Lake, New Jersey all rights reserved. *Actual price determined by dealer. Price excludes taxes, license, options and handling charge. Prices and specifications subject to change without notice.

Engine		Wheels and Tires	
Туре	Water cooled twin cylinder 4 stroke	Front Wheel	3.50 x 17 cast aluminum
Bore x Stroke	82 mm x 76 mm	Rear Wheel	5.50 x 17 cast aluminum
Displacement	798 cc	Front Tire	120/70 x ZR 17
Horsepower	90 bhp @ 8000 rpm	Rear Tire	180/55 x ZR 17
Torque	63 lb/ft @ 5800 rpm	Dimensions	
Compression Ratio	12.0 :1	Overall Length	84.5 inches
Valve Gear	DOHC, rocker arms	Overall Width	33.9 inches
Valves	2 x 32 mm intake / 2 x 27.5 mm exhaust	Wheelbase	60.1 inches
Valves / Cylinder	4	Ground Clearance	6.3 inches
Engine Oil Capacity	3.2 quarts	Seat Height	31.1 inches
Engine Management	Electronic Fuel Injection	Steering Angle	64.0 degrees
Fuel Requirement	Premium Unleaded	Front Wheel Trail	3.9 inches
Fuel Tank	PE/PA, internal pump and internal filter	Weight - Dry	397 lbs. excluding options & accessories
Fuel Capacity	3.9 U.S. gallons including 1 gallon reserve	Weight - Wet	444 lbs.
Charging System	400 Watts @ 14 Volts	Maximum Load	891 lbs. GVWR
Battery	12 Volts 7 Amps/hour maintenance-free	Available Colors	
Cooling System	50/50 water/anti-freeze mix, single radiator	Code Price	Description
Drivetrain		N0A \$100	Racing Blue Metallic Matt / Black Satin Gloss
Primary Drive	1:1.943	NB5 N/C	Light White
Clutch	Multi-disc, oil bath, mechanical actuation	ND8 \$0	Light White / Black Satin Gloss
1st Gear Ratio	2.46:1	ND9 \$100	Racing Blue Metallic Matt / Light White
2nd Gear Ratio	1.75:1	Standard Equipment	
3rd Gear Ratio	1.38:1	N/C	On Board Computer
4th Gear Ratio	1.23:1	N/C	BMW Motorrad ABS
5th Gear Ratio	1.13:1	N/C	Heated Grips
6th Gear Ratio	1.04:1	N/C	ASC (Automatic Stability Control/traction control)
Final Drive System	Chain	Available Equipment	
Final Drive Ratio	2.35:1	137 \$PKG	LED Rear Light (only w/ Dynamic Package)
Frame and Suspe	ension	203 \$295	Dynamic Package (includes 137, 580, 602)
Frame	Aluminum bridge, engine partly load bearing	416 \$350	Electronic Suspension Adjustment (ESA)
Front Suspension	Upside-down telescopic fork	530 \$250	Tire Pressure Monitor (TPM)
Front Travel	4.9 inches	580 \$PKG	Engine Spoiler (only w/ Dynamic Package)
Rear Suspension	Double sided aluminum swingarm	602 \$PKG	Pillion Seat Cover (only w/ Dynamic Package)
Rear Travel	4.9 inches	603 \$395	Anti-Theft Alarm
Brakes		764 \$50	Accessory Socket
Brake System	BMW Motorrad ABS - Standard	774 \$0	Low Seat (30.3")
Front Brakes	Dual floating discs, four-piston radial calipers	775 \$145	Comfort Seat
Front Rotor	12.6 inch dual floating rotors		
Rear Brake	Single disc, single-piston floating caliper		
		_	